

Model


2606

EVS™

cyclonic
bagless

The Power Unit, 'the heart of the ducted cleaning system' is constructed only with Quality Materials and Workmanship, assuring years of trouble free vacuuming.

Power Unit Features

- ✓ Injected molded from high impact, high temperature ABS polycarbonate and polypropylene plastics,
 - ✓ - provides greater strength and durability.
 - ✓ - will not dent and will last a house time.
 - ✓ - rust and corrosion proof.
 - ✓ - excellent for areas where there is excessive humidity and ideal for coastal areas.
- ✓ Right & Left Entry points for connection of ducting pipe to unit.
- ✓ Cyclonic Filtration System utilising HFPC filter for added motor protection.
- ✓ Also offering Dual Filtration Compatibility; allowing optional Disposable Filter bag to be fitted if required with Bag Conversion Kit.
- ✓ Large capacity dirt receptacle easily emptied by releasing two clamping latches that provide a hermetic vacuum seal between motor base housing and dirt receptacle.
- ✓ Single printed circuit board control module complete with,
 - ✓ - on/off switch for operating inlet point on power unit.
 - ✓ - terminals for extra low voltage remote connections for inlet points inside house.
 - ✓ - IEC type socket and lead for power mains connection.
 - ✓ - dual LED technology status indicators for visual standby and operating modes.
- ✓ Manufactured to meet with all relevant Electrical Safety Standards in Australia and complies with the EMC emission standard AS/NZS 1044. Power units are all marked with the approved marking,  logo, and registration number N1461.
- ✓ Powered by High Efficiency Ametek 2 Stage 183mm Turbine By-pass Industrial grade vacuum motor.
- ✓ Tangential discharge of outgoing air allows unit to be fitted with Silencer for added exhaust noise reduction and allows for venting to outside for 100% filtration.




Est. 1981
Vacuuming Systems
(Aust) Pty Ltd
www.evsaustr.com.au

CLEANER LIVING



Model 2606


EVS™

183mm Base Turbine
2 Fan Stages
AMETEK® Quality Motor Inside

SPECIFICATIONS

Model	2606
Vacuum Motor Specifications	
Tangential By-pass discharge	●
Flow Through discharge	
Double ball bearings	●
Diameter of Motor mm	183
Air Watts	400
Airflow l/s (max.)	48
Sealed Vacuum mm H ₂ O (max.)	2795
RPM @19mm working orifice	15500
Label Rated Electrical Watts	1400
Noise Level dbA with Silencer @ 3m	66.5
Temperature Sensitive Thermal Protector	
Control Circuit 12 V DC	●
Control Current 100mA	●
Nominal Voltage 240 V AC	●
Nominal Frequency 50 Hertz	●
Power Unit Physical Specifications	
Overall Height (mm)	810
Overall Diameter (mm)	310
Overall Weight (kg)	8.4
Dual Filtration Compatible System	●
Cyclonic Filtration (Standard)	●
HFPC Filter Cartridge	●
Filter Bag Filtration	
Silencer for Exhaust	●
Left & Right ducting entry points	●
Direct Inlet point with On/Off switch	●
Wall Mounting of Power Unit	●
Body Housing Construction	ABS
Dirt Capacity litres	25

Specifications Subject to Change without Notice



Available from,



www.evsaust.com.au

CLEANER LIVING

VER0210VAC2606



E.O.& E, Printed in Australia ©

